



Product Description
ELKALUB GLS 75/N2
Multipurpose Grease for Bearings

GLS 75/N2 is a lithium-saponified multipurpose grease, which is highly resistant to pressure, adhesive and resistant to oxidation. **GLS 75/N2** has a special ELKALUB additivation for the lubrication of roller and slide bearings (under medium up to heavy loads) for temperatures from -20 up to +120° C.

GLS 75/N2 is particularly suited for points of lubrication with high centrifugal losses and where there is danger of the lubricant being washed out by water. The grease can be used up to a speed factor (ndm*) of about 400.000.

Technical data

Characterisation according to DIN 51 502	KP2K-20
Chemical composition	Mineral oil, lithium soap, additives
Application	Long-term grease which is resistant to oxidation and highly resistant to pressure
Appearance	beige, long-fibrous
Temperature of use	-20 C - +120° C (short-term +150° C) (standard values; consultation necessary).
NLGI class	2
Worked penetration	270+/- 15 units
Water resistance	(0-1)-90
Dropping point	> 180° C
Oil separation	K < 2
Density (T)	0,92-0,93
Base oil viscosity	ISO VG 100 [97 mm ² /s (40° C); 11 mm ² /s (100° C)]

Notes: * With GLG 16 (NLGI classes from 1 to 000) we have a lithium-saponified gear grease with a good resistance to oxidation and an increased resistance to water, excellent sliding-friction and high load carrying capacities.

* GLL 7 is a lithium-multipurpose grease, with similar properties.

* $N_{dm} = \frac{1}{2} (D+d) \times n$

D = Inner diameter of the bearing (mm)

d = Outer diameter of the bearing (mm)

n = revolutions per minute

These data are issued in good faith and reflect our knowledge of today. We reserve the right to modify and/or supplement them.

Vöhringen, 15.04.98/AP

Revision: 06.06.2004 AP